

SC-31-0100-0001-99

SmartCell Red Sounder

Overview

The SmartCell Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-31-0100-0001-99

SmartCell Red Sounder

Technical specifications

General

Wireless frequency 868 MHz

Electrical

Batteries 3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)

Sounder

Output level 95 dB(A) at 1 m max.

Output level adjustment High or low

Selectable tones 32

Physical

Physical dimensions 110 x 72 mm (Ø x D)

Net weight 0.2 kg

Colour Red

Mounting type Wall mount

Mounting position Wall

Environmental

Operating temperature -10 to +55°C

Storage temperature -10 to +30°C (with batteries)
-10 to +55°C (without batteries)

Relative humidity 95% noncondensing max.

Environment Indoor

IP rating IP21C

Regulatory

Compliance CE

Certification CPR

Standards EN54-3
EN54-13
EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit ie.firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 10:31