

ZP755HA-2P

Ziton ZP7 series horn sounder, polar white

General

ZP755HA-2P is a POLAR WHITE addressable horn sounder designed for use with ZP addressable fire alarm systems. Designed with dual front and rear sound paths, it provides an 'all around' sound output - ideal for open area coverage.

Installed directly onto and powered by the ZP wiring loop, the ZP755HA-2 sounders enable the system designer to offer a complete ZP addressable system on a single pair of wires. Installation time and costs are further reduced as the moulding plugs directly into a first fix base – eliminating the need for any internal connections.

The units high efficiency acoustic design, together with a low energy 'sound gun' transducer, enables up to 40 sounders to be connected to a one kilometre loop of 1.5mm² cable, with a wiring run of 50 metres to the first device.

Self test facility

The range features a unique self test facility - automatically activated during routine sounder testing. A built in microphone circuit measures sound output and automatically signals the sounder address and location to the control panel, should the output test fail.

In systems where loop lengths or current requirements are excessive, ZP755 sounders can be powered directly from an external power supply. All ZP755 sounders incorporate switch settings enabling them to be assigned a unique address, which is polled by the panel every two seconds.

Range of sound outputs

Continuous, intermittent and two-tone outputs are available from which any combination can be chosen to provide alert and evacuate, two stage alarms. Sound types comply with most international codes (e.g. BS 5839 Part 1 recommended frequencies).

ZP755HA-2 sounders produce a sound output of up to 92 dBA (tested at 1 metre). The volume setting can be reduced for areas where a lower sound output is required.

Moulded in high impact thermoplastic, the sounders are available in either polar white, red or white.



Details

- Wide 'all around' sound distribution
- Microphone self test facility
- Plug in base – no direct wiring connections
- Up to 50 sounders directly on the loop wiring
- High efficiency sound gun transducer
- Synchronised outputs
- EN54:3 approved and CPR certified

ZP755HA-2P

Ziton ZP7 series horn sounder, polar white

Technical specifications

General

Compatibility	ZP7 series addressable systems
---------------	--------------------------------

Electrical

Operating voltage	19.5 to 20.5 V (from the loop)
	18 to 30 VDC (from an external supply)
Current consumption	820 μ A Quiescent (when loop powered)
	6.4 mA Active (when loop powered)
	470 μ A Quiescent (when externally powered)
	500 μ A Active (when externally powered)

Sounder

Output level	<90 dB(A) (tone dependent)
Output level adjustment	Supported
Selectable tones	Use configurable
Synchronization	Supported

Physical

Physical dimensions	127 x 113 mm (\varnothing x H)
Net weight	275 g
Colour	Polar white
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Material	Moulded thermoplastic

Environmental

Vandal proof	No
Operating temperature	-10 to +60°C
Storage temperature	-20 to +70°C
Relative humidity	10 to 95%
Environment	Indoor
IP rating	IP21C

Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54-3

Devices per loop (max)

50 (1km loop of 1.5mm ² cable, 50 m to first device)

Wiring



2 core loop

Monitoring

Open/short circuit, sound output, removal, device type

Addressing method

7 way dipswitch



4160-01



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit ie.firesecurityproducts.com online or contact your sales representative.

Last updated on 22 May 2023 - 13:00