

AD105P-0100

Alarmline II Digital LHD Cable 105°C (221°F) w/ Polypropylene Sheath - 100m

General

The AD105P-0100 is a Digital Linear Heat Detection (LHD) cable with a 105°C (221°F) fixed temperature activation rating. It has a Polypropylene outer sheath providing increased chemical protection in caustic environments and is supplied in 100m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' , 'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD105P-0100

Alarmline II Digital LHD Cable 105°C (221°F) w/ Polypropylene Sheath - 100m

Technical specifications

Electrical

Operating voltage	0 to 30VAC, 0 to 42VDC
-------------------	------------------------

Operating voltage	0 to 30VAC, 0 to 42VDC
-------------------	------------------------

Detection

Alarm temperature (typical)	+105°C
--------------------------------	--------

Conductor

Resistance	91 Ω/km (27.7 Ω/1000ft.)
------------	--------------------------

Capacitance	< 73 pF/m (<22 pF/ft.)
-------------	------------------------

Inductance	< 1.65 μH/m (<0.5 μH/ft.)
------------	---------------------------

Physical

Net weight	2.72 kg
------------	---------

Colour	White
--------	-------

Mounting type	Screw mount
---------------	-------------

Environmental

Relative humidity	0 to 100% noncondensing
-------------------	-------------------------

Environment	Indoor, Outdoor
-------------	-----------------

Protection	Polypropylene Sheath
------------	----------------------

Ambient temperature (max)	69°C (156°F)
------------------------------	--------------

Relative humidity	0% to 100%
-------------------	------------

Regulatory

Certification	CE
---------------	----

Mechanical

Outside diameter (Nominal)	4.5mm ± 0.12mm
-------------------------------	----------------

No of cores	2
-------------	---

Colour	White
--------	-------

Weight	2.72kg
--------	--------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 April 2023 - 18:37