



# BS133N

Battery 12 V 65 Ah



## Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS133N

## Battery 12 V 65 Ah

### Spécifications techniques

---

#### Généralités

---

Product type	Sealed lead acid battery
--------------	--------------------------

---

#### Caractéristiques électriques

---

Nominal voltage	12 V
Nominal capacity	65 Ah
Internal approx. resistance	10 mOhm

---

#### Charge / décharge

---

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	19.5A
Max. discharge current	325 A

---

#### Température

---

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

---

#### Caractéristiques physiques

---

Physical dimensions	350 x 166 x 174 mm
Net weight	23.0 kg
Shipping weight	23.0 kg
Material	ABS
Terminal type	MS bolt & nuts

---

#### Environnement

---

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

---

#### Regulatory

---

Compliance	CE, RoHS 2, WEEE
Certification	VdS

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 24 August 2022 - 12:21