

ACA-B706-025

LHD Cable Accessory - Bracket "7", 60 mm (2.4") (Zintec) w/ Sleeve - Qty 25

Pipe Clip

The ACA-B706 series 7-bracket (pipe clip) is designed to utilise existing pipework running through the protected area as a fixture for the liner heat detection cable. The ACA-B706 is designed to fit any pipe diameter. A silicon protection sleeve is supplied with the unit to protect the linear heat cable when fastened to the bracket.

Installation

The ACA-B706 should be fitted to the underside of the pipe and secured in place using suitable cable ties or strapping. The hole in the end of the bracket allows for the securing of the sensor cable using a silicone sleeve and cable tie. Alternatively an I-bracket (distance piece) may be connected to the 7-bracket to extend the position of the sensor cable. Without an extension the 7-bracket (pipe clip) supports the sensor cable approx. 60mm below the pipe.

Recommended spacing: 1m



Details

- Easy installation of linear heat cable
- For use on existing pipes in the area
- Available in zintec
- Available in quantities of 25

ACA-B706-025

LHD Cable Accessory - Bracket "7", 60 mm (2.4") (Zintec) w/ Sleeve - Qty 25

Technical specifications

Physical

Physical dimensions	20 x 60 x 50 mm (W x H X D)
Net weight	850 g
Mounting type	Clip on

Environmental

Environment	Indoor, Outdoor
-------------	-----------------

Dimensions (h x w x d)

	60 x 20 x 50 mm
--	-----------------

- ACA-B706-025

Weight	850g
Material	Zintec
Quantity	25

- ACA-B706-100

Weight	3.4 kg
Material	Zintec
Quantity	100

- ACA-B706SS-025

Weight	580g
Material	Stainless Steel
Quantity	25

- ACA-B706SS-100

Weight	2.3kg
Material	Stainless Steel
Quantity	100



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 5 April 2023 - 18:37