



AS363M

Sounder, Multi Tone, Shallow Base, Mains Powered

General

The AS363M is a general purpose, mains powered, electronic sounder for alarm applications.

Efficient and versatile

The AS363M provide high sound output at a low current, thus reducing power requirements and system cost. The AS363M sounder is supplied with a volume control as standard, allowing final audio adjustments to be made during installation.

With a choice of 32 different tones (see tones table in manual), which are switch selectable, the required tone can be selected during installation.

The mechanism for locking the sounder to the base, can be activated if required. Once activated, a special tool is required to remove the sounder from the base.



Details

- High sound output
- 32 Tones user selectable
- Automatic synchronisation
- Volume control
- Anti-Tamper locking mechanism
- Shallow mounting base

AS363M

Sounder, Multi Tone, Shallow Base, Mains Powered

Technical specifications

Electrical

Operating voltage 110/220VAC 50/60Hz

Current consumption 80 mA (depends on selected tone)

Sounder

Output level Sound output at 1 m (depends on selected tone):
89 to 102dB(A)

Selectable tones 32

Synchronization Phased start (automatic)

Physical

Physical dimensions 100 x 81 mm (Ø x D) (shallow base)

Net weight 215 g

Colour Red

Material High impact polycarbonate

Environmental

Operating temperature -25 to +55°C

Environment Indoor

IP rating IP21

Operation

Continuous



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 7 April 2023 - 14:09