

DMN700Y03-KITR

MCP Yellow, Free Contact, Surface Mount, Resettable, Protection Cover

General

DMN700Y03-KITR is a yellow manual call point for surface mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a resettable break glass and test key.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

DMN700Y03-KITR

MCP Yellow, Free Contact, Surface Mount, Resettable, Protection Cover

Technical specifications

Isolation

Series resistance	NA
-------------------	----

Physical

Physical dimensions	92 x 115 x 59 mm (W x H x D)
---------------------	------------------------------

Net weight	110 g
------------	-------

Colour	Yellow
--------	--------

Mounting type	Surface mount
---------------	---------------

Material (body)	PC/ABS
-----------------	--------

Environmental

Operating temperature	-10 to +55°C
-----------------------	--------------

Storage temperature	-10 to +55°C
---------------------	--------------

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

Environment	Indoor
-------------	--------

IP rating	IP24D
-----------	-------

Cable Termination

0.5 to 2.5 mm ²

Max. contact rating (resistive load)

2A @ 30 VDC



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit ie.firesecurityproducts.com online or contact your sales representative.

Last updated on 4 May 2023 - 17:07