

# DMN700W03-KITR

## MCP White, Free Contact, Surface Mount, Resettable, Protection Cover

### General

---

DMN700W03-KITR is a white manual call point for surface mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a resettable break glass and test key.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



### Details

---

- Enhanced aesthetics
- Easy to install (plug and play)
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

# DMN700W03-KITR

MCP White, Free Contact, Surface Mount, Resettable, Protection Cover

## Technical specifications

---

### Isolation

---

|                   |    |
|-------------------|----|
| Series resistance | NA |
|-------------------|----|

---

### Physical

---

|                     |                              |
|---------------------|------------------------------|
| Physical dimensions | 92 x 115 x 59 mm (W x H x D) |
|---------------------|------------------------------|

---

|            |       |
|------------|-------|
| Net weight | 110 g |
|------------|-------|

---

|        |       |
|--------|-------|
| Colour | White |
|--------|-------|

---

|               |               |
|---------------|---------------|
| Mounting type | Surface mount |
|---------------|---------------|

---

|                 |        |
|-----------------|--------|
| Material (body) | PC/ABS |
|-----------------|--------|

---

### Environmental

---

|                       |              |
|-----------------------|--------------|
| Operating temperature | -10 to +55°C |
|-----------------------|--------------|

---

|                     |              |
|---------------------|--------------|
| Storage temperature | -10 to +55°C |
|---------------------|--------------|

---

|                   |                        |
|-------------------|------------------------|
| Relative humidity | 0 to 95% noncondensing |
|-------------------|------------------------|

---

|             |        |
|-------------|--------|
| Environment | Indoor |
|-------------|--------|

---

|           |       |
|-----------|-------|
| IP rating | IP24D |
|-----------|-------|

---

### Cable Termination

---

|  |                            |
|--|----------------------------|
|  | 0.5 to 2.5 mm <sup>2</sup> |
|--|----------------------------|

---

### Max. contact rating (resistive load)

---

|  |             |
|--|-------------|
|  | 2A @ 30 VDC |
|--|-------------|

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [ie.firesecurityproducts.com](http://ie.firesecurityproducts.com) online or contact your sales representative.

Last updated on 4 May 2023 - 17:07